

RUSTLER

HEAVY HARROW

Base Size	55 feet (16.76 m)	68 feet (20.72 m)	78 feet (23.77 m)
Harrows - Sections 5 Bars - 18" (460mm) Spacing Between Rows - 2 er Pipe	5 - 11' (3.4m)	2 - 6 1/2' (2 m) 5 - 11' (3.4 m)	7 - 11' (3.4m)
Tines - Straight with 4" high wear edge 9/16" x 28 (1.4 cm x 69 cm)	Standard	Standard	Standard
Hydraulic Tine Adjustment	Standard	Standard	Standard
Main Frame -Single Axle -Tire Size -	(2) 6.5L x 16.1 10 ply rating	(2) 6.5L x 16.1 10 ply rating	(2) 6.5L x 16.1 10 ply rating
Wing Axle (1 per wing) - Tire Size	(2) 2.5L x 15 8 ply rating	(2) 2.5L x 15 8 ply rating	(2) 2.5L x 15 8 ply rating
Weight	11,950 lbs. (5,420 kg)	13,560 lbs. (6,151 kg)	14,720 lbs. (6,677 kg)
Transport Length	44' 8" (13.7 m)	51' 8" (15.8 m)	55' 10" (17.0 m)
Transport Height	11' 8" (3.6 m)	11' 8" (3.6 m)	11' 8" (3.6 m)
Transport Width	14' 9" (4.5 m)	14' 9" (4.5 m)	14' 9" (4.5 m)
Cart Frame - 8" (20.3 cm) x 4" (10 cm) Structural Tubing	Standard		
Main Frame - 8" (20.3 cm) x 8" (20.3 cm) Structural Tubing	Standard		
Wing Frames - 8" (20.3 cm) x 8" (20.3 cm) Structural Tubing	Standard		
Safety Chain	Standard		
Safety Lights	Standard		
Harrow Arms	Self-Levelling Parallel Linkage		
Harrow Tine Length	28" (69 cm)		
Harrow Tine Diameter	9/16" (1.4 cm)		
Harrow Tine Spacing	2.75 inches (7 cm)		
Harrow Tine Angle Degree Range	40 - 85		
Hydraulics	Requires 3 control valves		



MORRIS