

Base Size	3 Frame Models		5 Frame Models		
	25' (7.62 m)	31' (9.45 m)	80' (24.38 m)	90' (27.43 m)	
Weight - 10" Spacing 25.40 cm Spacing	14,738 lb 6,685 kg	16,025 lb 7,269 kg	NA NA	NA NA	
	- 12" Spacing 30.48 cm Spacing	13,933 lb 6,320 kg	15,155 lb 6,874 kg	38,140 lb 17,300 kg	43,000 lb 19,505 kg
Working Width	- 10" (25.40 cm) Spacing	25' (7.62 m)	30' (9.14 m)	NA	NA
	- 12" (30.48 cm) Spacing	25' (7.62 m)	31' (9.45 m)	80' (24.38 m)	90' (27.43 m)
Number of Shanks	- 10" (25.40 cm) Spacing	30	36	NA	NA
	- 12" (30.48 cm) Spacing	25	31	80	90
Frame Width	- Main	5' (1.52 m)	5' (1.52 m)	21' (6.40 m)	21' (6.40 m)
	- Wing Inner	10' (3.05 m)	13' (3.96 m)	15' (4.57 m)	15' (4.57 m)
	- Wing Outer	N/A	N/A	14.45 (4.40 m)	18.92' (5.77 m)
Transport Position	- Width	9' 10" (3.00 m)	9' 10" (3.00 m)	25' (7.62 m)	25' (7.62 m)
	- Height	13' 9" (4.19 m)	16' 2" (4.93 m)	18' 1" (5.51 m)	18' 1" (5.51 m)
	- Length	31' 6" (9.60 m)	31' 6" (9.60 m)	34' 10" (10.62 m)	34' 10" (10.62 m)
Tires	- Main Frame Wheels	(4) 12.5Lx15 FI Load Range F	(4) 12.5Lx15 FI Load Range F	(8) 16.5x16.1 FI Load Range E	(8) 16.5x16.1 FI Load Range E
	- Wing Frame Front Castor Wheels	Single Castor (2) 12.5SLx15 12 Ply Rating	Single Castor (2) 12.5SLx15 12 Ply Rating	Dual Castor (8) 12.5SLx15 12 Ply Rating	Dual Castor (8) 12.5SLx15 12 Ply Rating
	- Wing Frame Rear Wheels	(1 per wing) (2) 12.5SLx15 12 Ply Rating	(1 per wing) (2) 12.5SLx15 12 Ply Rating	(2 per wing) (8) 12.5SLx15 12 Ply Rating	(2 per wing) (8) 12.5SLx15 12 Ply Rating
	- Optional Main Frame Wheels	NA	NA	NA	NA
	Opener - Trip Out Force	Minimum 300 lbs (136 kg) at 450 psi (3102 kPa) to Maximum 700 lbs (317 kg) at 1200 psi (8274 kPa)			
- Packing Force	80 lbs to 200 lbs (36 kg - 91 kg)				
- Packer Wheel	4.50" x 16" Semi Pneumatic Otico tire 4.80" x 16" Semi Pneumatic or Pneumatic 5.50" x 16" Semi Pneumatic Otico tire 5.50" x 16" Semi-Pneumatic 4.00" x 16" "V" Crown				
Opener to Ground Clearance	12" (30.48 cm)				
Frame to Ground Clearance	32" (81.28 cm)				
Frame Depth	94" (238.76 cm) center to center				
Rank to Rank Spacing	47" (119.38 cm) center to center				
Number of Ranks	3 Rows				
Shank to Shank Spacing	30" (76.20 cm) on 10" (25.40 cm) Spacing 36" (91.44 cm) on 12" (30.48 cm) Spacing				
Weight Kit	Optional				
Safety Lights	Standard				
Hitch Clevis	Standard - Category 4		Optional - Category 5		
Safety Chain	Standard				

Specifications are estimates and subject to change.

