

RAZR

DISC DRILL

| Base Size | 3 Frame Models | 5 Frame Models | |
|---|---|--|--|
| | 40' (12.19 m) | 50' (15.24 m) | 60' (18.29) |
| Weight - 7.5" (19 cm) Spacing - Single Shoot - 10" (25.4 cm) Spacing - 15" (38.1 cm) Spacing | 30313 lbs (13750 kg) | 42768 lbs (19399 kg) | 51827 lbs (23508 kg) |
| | 27081 lbs (12284 kg) | 38344 lbs (17393 kg) | 46514 lbs (21098 kg) |
| | 24051 lbs (10909 kg) | 34890 lbs (15826 kg) | 42333 lbs (19202 kg) |
| Working Width - 7.5" (19 cm) - 10" (25.4 cm) - 15" (38.1 cm) | 38' 4.5" (12 m) | 49' 4.5" (15.05 m) | 59' 4.5" (18.10 m) |
| | 39' 2" (11.93 m) | 49' 2" (14.99 m) | 59' 2" (18.03 m) |
| | 40' (12.19 m) | 50' (15.24 m) | 60' (18.29 m) |
| Number of Openers - 7.5" (19 cm) - Single Shoot - 10" (25.4 cm) - 15" (38.1 cm) | 63 | 79 | 95 |
| | 47 | 59 | 71 |
| | 32 | 40 | 48 |
| Number of Openers - 7.5" (19 cm) - Double Shoot - 10" (25.4 cm) - 15" (38.1 cm) | NA | NA | NA |
| | 71 | 89 | 107 |
| | NA | NA | NA |
| Frame Width - Main - Wing Inner - Wing Outer | 14' 3.5" (4.356m) | 14' 3.5" (4.356m) | 14' 3.5" (4.356m) |
| | 11' 11.5" (3.645m) | 11' 11.5" (3.645m) | 11' 11.5" (3.645m) |
| | NA | 5' 4.84" (1.647m) | 9' 11.25" (3.029m) |
| Transport Position - Width - Height - Length | 20' 3" (6.17m) | 20' 3" (6.17m) | 20' 3" (6.17m) |
| | 15' 11" (4.85 m) | 15' 11" (4.85 m) | 15' 11" (4.85 m) |
| | 31' 7" (9.63 m) | 35' 8" (10.87 m) | 35' 8" (10.87 m) |
| Tires - Main Frame Wheels - Wing Frame Front Castor Wheels - Wing Frame Rear Wheels | (8) 16.5x16.1 FI Load Range E | (8) 16.5x16.1 FI Load Range E | (8) 16.5x16.1 FI Load Range E |
| | Dual Castor (8) 12.5SLx15 12 Ply Rating | Dual Castor (8) 12.5SLx15 12 Ply Rating | Dual Castor (8) 12.5SLx15 12 Ply Rating |
| | (2 per wing) (8) 12.5SLx15 12 Ply Rating | (2 per wing) (8) 12.5SLx15 12 Ply Rating | (2 per wing) (8) 12.5SLx15 12 Ply Rating |
| Opener - Disc Down Force - Packing Force - Disc Size - Gauge Wheel - Packer Wheel | Adjustable from 200 lbs (90.7 kg) to a maximum of 7.5" Spacing – 465 lbs* (210.9 kg)* 10" Spacing – 550 lbs* (249.5 kg)* 15" Spacing – 690 lbs (313 kg) *Limited by available frame weight | | |
| | Increases proportionally with Disc Down Force - 66 lbs to 150 lbs (30 kg - 68 kg) | | |
| | 1/4 x 20" (0.63 cm x 50.8 cm) at 5 Degree Angle | | |
| | 4 1/2 x 16 x 3 Spoke | | |
| | 4 x 12 Dual Rib | | |
| Opener to Ground Clearance | 10" (25.4 cm) | | |
| Rank to Rank Spacing | 59" center to center | | |
| Number of Ranks | 2 Rows | | |
| Shank to Shank Spacing | 15" (38.1 cm) on 7.5" (19 cm) Spacing 20" (50.8 cm) on 10" (25.4 cm) Spacing 30" (76.2 cm) on 15" (38.1 cm) Spacing | | |
| Weight Kit | Optional | | |
| Safety Lights | Standard | | |
| Hitch Clevis | Standard - Category 4 Optional - Category 5 | | |
| Safety Chain | Standard | | |

Specifications are estimates and subject to change.



MORRIS